


EDD

NOTES:
UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE ± .010" [.254mm].


DRAWING NO.:	REV.
81A3027TC-*	A



MATERIAL:
SUBSTRATE: BERYLLIUM OXIDE
COVER: ALUMINA
TAB: BERYLLIUM COPPER PER ASTM B194
RESISTIVE FILM: THIN FILM

FINISH:
RoHS COMPLIANT
GROUND PLATE: SILVER PLATED
TERMINALS: SILVER PLATED

ELECTRICAL:
*DC RESISTANCE: 10-150 OHMS
AVERAGE POWER: 500 WATTS
CAPACITANCE: 1.50 pF
TEMPERATURE COEFFICIENT: ± 200 PPM/°C MAX
OPERATING TEMPERATURE: -55° TO +150° C

				EN# 11-0010	APVD	DATE	REFERENCE	 8851 OLD KANSAS AVE. STUART, FL. 34997 772-286-9300			
				UNLESS OTHERWISE SPECIFIED 1. DO NOT SCALE DRAWING 2. DIMENSIONS ARE IN INCHES 3. DIMENSIONS ARE AFTER PLATING 4. CORNERS, EDGES AND FILLETS: R MAX 5. SURFACE ROUGHNESS: 6. REMOVE ALL BURRS			CATALOG	TITLE TAB & COVER, RESISTOR, 500 WATT			
							MATERIAL			-	
				TOLERANCES .X ± .XX ± .XXX ± ANGLES X° ±			FINISH	-			
				THE INFORMATION CONTAINED HEREIN IS: (A) CONSIDERED PROPRIETARY TO FLORIDA RF LABS INC.; (B) PROTECTED BY COPYRIGHT OWNED BY FLORIDA RF LABS INC.; (C) CONSIDERED A "WORK FOR HIRE" UNDER COPYRIGHT LAW; (D) PROTECTED BY TRADE SECRET LAWS WHICH MAKE ILLEGAL THE MISAPPROPRIATION OF THIS INFORMATION; AND (E) IS TO BE USED SOLELY FOR THE PURPOSE WHICH IT IS SUPPLIED. THIS INFORMATION SHALL NOT BE DISCLOSED IN WHOLE OR IN PART, TO ANY PARTY, FOR ANY REASON WITHOUT THE EXPRESS WRITTEN CONSENT OF A QUALIFIED EXECUTIVE OF FLORIDA RF LABS INC.			SCALE	CAGE CODE ID NO.	SIZE	DRAWING NO.:	REV.
A	EN 15-2041	NOA 11/30/15					3/1	2Y194	A	81A3027TC-*	A
REV.	DESCRIPTION	DRAWN	APVD.	MFG:	CHKD.:	DRAWN: JNK 01/18/11	SHEET 2 OF 2				